

Direct Reading Precision Attenuators (Series 510)

上海馥莱电子有限公司
电话: 021-5291 8556
手机: 13764441515(微信)
邮箱: sales@fulai-elec.com
www.fulai-elec.com

Mi-Wave's 510 Series Direct-reading Precision Attenuators provide 0 to 60 dB of calibrated attenuation by rotation of a resistive vane mounted in a circular waveguide section. These units are often referred to as precision rotary vane attenuators.



510(34)/1530

22 – 33 GHz, WR-34, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510A/599

26.5 – 40 GHz, WR-28, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510B/383

33 – 50 GHz, WR-22, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510U/383

40 – 60 GHz, WR-19, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510V/385

50 – 75 GHz, WR-15, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510E/387

60 – 90 GHz, WR-12, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510W/387

75 – 110 GHz, WR-10, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510F/387

90 – 140 GHz, WR-8, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510D/387

110 – 170 GHz, WR-6, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510G/387

140 – 220 GHz, WR-5, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510H-387

170 – 260 GHz, WR-4, Attenuation Range to 60 dB

[VIEW PRODUCT](#)



510J/387

220 – 325 GHz, WR-3, Attenuation Range to 60 dB

[VIEW PRODUCT](#)