

2.92mm DC Block 50kHz-40GHz

AT-DC-29X29X


Feature

2.92mm to 2.92mm DC Block

Specified 16kHz-40GHz

Low Insertion Loss

Excellent Broadband VSWR



Specifications -

Specifications guaranteed from -45 to +85°C, measured in a 50Ω system

Parameter	Frequency Range	Min	Typ	Max	Unit
Insertion Loss	50kHz-40GHz		0.7	1.4	dB
VSWR			1.2	1.3	
Voltage			16		V
RF Power			1		W

Environmental

-55 C to +125 C

Corrosion: MIL-STD 202

Vibration: MIL-STD 202

Materials

Body: SU304 Polished & Passivated

Center Contact: Beryllium Copper Gold Plated

Insulators: PEI


Mechanical

1000 Cycles Min

Order Information

Connector #1	Connector #2	Part Number
2.92mm Male	2.92mm Female	AT-DC-29M29F
2.92mm Female	2.92mm Female	AT-DC-29F29F
2.92mm Male	2.92mm Male	AT-DC-29M29M

Dimension



AT Microwave

RM1204,NO.2911,North Zhongshan RD, Putuo District , Shanghai ,China, 200063

Tel:+8621-5291 8556 Email:sales@atmicrowave.com www.atmicrowave.com