

超高电压 100V 的偏置器 Bias Tee

Frequency Range		Insertion Loss (dB) max.	Current (mA) max.	Power (watts) max.	Voltage (Vdc) max.	Isolation (dB) min.	VSWR max.	Package Type	型号
Min	Max								
50 MHz	800 MHz	0.6	6000	15	100	25	1.20:1	Surface	BT-10-E
425 MHz	800 MHz	0.6	8000	15	100	25	1.50:1	SMA	BT-11-411
10 MHz	1000 MHz	0.5	1000	5	100	25	1.20:1	SMA	BT-20-410F
10 MHz	1000 MHz	0.5	1000	5	100	25	1.20:1	SMA	BT-20-411
10 MHz	1000 MHz	0.5	1000	5	100	25	1.20:1	SMA	BT-20-414
10 MHz	1000 MHz	0.5	1000	5	100	25	1.20:1	Surface	BT-20-E
800 MHz	1000 MHz	0.5	5000	10	100	30	1.50:1	SMA	BT-21-410F
800 MHz	1000 MHz	0.5	5000	10	100	30	1.50:1	SMA	BT-21-411
800 MHz	1000 MHz	0.5	5000	10	100	30	1.50:1	SMA	BT-21-414
800 MHz	1000 MHz	0.5	5000	10	100	30	1.50:1	Surface	BT-21-E
1700 MHz	2000 MHz	0.5	5000	10	100	30	1.50:1	SMA	BT-22-410F
1700 MHz	2000 MHz	0.5	5000	10	100	30	1.50:1	SMA	BT-22-411
1700 MHz	2000 MHz	0.5	5000	10	100	30	1.50:1	SMA	BT-22-414
1700 MHz	2000 MHz	0.5	5000	10	100	30	1.50:1	Surface	BT-22-E
10 MHz	6000 MHz	1.8	4000	10	100	25	1.50:1	SMA	BT-40-402D
10 MHz	6000 MHz	1.8	4000	10	100	25	1.50:1	SMA	BT-40-402S



更多信息，请联系我们：

地址：上海市普陀区祁连山南路 2888 号耀光中环国际 A 座 9H 室

Tel: 021-5291 8556, Fax: 021-6260 7783

www.fulai-elec.com

Email: sales@fulai-elec.com