

Digital Controlled Phase Shifters

Frequency Range (GHz)		Insertion Loss (dB) max.	Number of Bits	Least Significant Bit (LSB)	Phase Range	VSWR (dB) max.	Connector Type	P/N
Min	Max							
0.05	0.06	5.0	8	1.4°	360°	1.50:1	SMA	DST-15-480/1S <input type="button" value="Add to RFQ"/>
0.25	0.50	6.0	8	1.4°	360°	1.80:1	SMA	DST-10-480/1S <input type="button" value="Add to RFQ"/>
0.50	1.00	4.5	8	1.4°	360°	1.80:1	SMA	DST-11-480/1S <input type="button" value="Add to RFQ"/>
1.25	1.35	3.5	8	1.4°	360°	1.80:1	SMA	DST-14-480/1S <input type="button" value="Add to RFQ"/>
1.00	2.00	4.5	8	1.4°	360°	1.80:1	SMA	DST-12-480/1S <input type="button" value="Add to RFQ"/>
2.00	4.00	6.0	8	1.4°	360°	1.80:1	SMA	DST-13-480/1S <input type="button" value="Add to RFQ"/>



Outline 480/1S
5.00" x 3.00" x 0.75"

Name: DST-10-480/1S
 Frequency Range: 0.25-0.5 GHz
 Insertion Loss: 6.0 dB max.
 Number of Bits: 8
 Least Significant Bit: 1.4° LSB
 Phase Range : 360°
 VSWR: 1.80:1 dB max.
 Connector Type: SMA



Outline 480/1S
5.00" x 3.00" x 0.75"

Name: DST-12-480/1S
 Frequency Range: 1-2 GHz
 Insertion Loss: 4.5 dB max.
 Number of Bits: 8
 Least Significant Bit: 1.4° LSB
 Phase Range : 360°
 VSWR: 1.80:1 dB max.
 Connector Type: SMA

更多信息，请联系我们：

地址：上海市普陀区祁连山南路 2888 号耀光中环国际 A 座 9H 室

Tel: 021-5291 8556, Fax: 021-6260 7783

www.fulai-elec.com

Email: sales@fulai-elec.com