



同轴偏置器（DC 端是 PIN 针）

Frequency Range		Insertion Loss (dB) max.	Current (mA) max.	Power (watts) max.	Voltage (Vdc) max.	Isolation (dB) min.	VSWR max.	Package Type	P/N
Min	Max								
10 MHz	6000 MHz	1.8	4000	10	100	25	1.50:1	SMA/Pin	BT-40-402D <input type="button" value="Add to RFQ"/>
500 MHz	10 GHz	1.0	200	1	50	30	1.50:1	SMA/Pin	BT-26-400D <input type="button" value="Add to RFQ"/>
5 GHz	12 GHz	0.8	250	1	50	30	1.50:1	SMA/Pin	BT-30-400D <input type="button" value="Add to RFQ"/>
100 kHz	12.4 GHz	1.5	700	1	50	40	1.60:1	SMA/Pin	BT-52-400D <input type="button" value="Add to RFQ"/>
8 GHz	15 GHz	1.0	200	1	50	35	1.50:1	SMA/Pin	BT-28-400D <input type="button" value="Add to RFQ"/>
100 kHz	18 GHz	2.0	700	1	50	40	1.60:1	SMA/Pin	BT-53-400D <input type="button" value="Add to RFQ"/>
300 MHz	18 GHz	1.5	500	1	50	25	1.60:1	SMA/Pin	BT-29-400D <input type="button" value="Add to RFQ"/>
30 kHz	27 GHz	2.2	500	1	25	40	1.80:1	SMA/Pin	BT-51-400D <input type="button" value="Add to RFQ"/>
30 kHz	40 GHz	3.0	500	1	25	30	1.80:1	SMA/Pin	BT-50-400D <input type="button" value="Add to RFQ"/>
30 kHz	70 GHz	4.0	500	1	25	30	2.00:1 Typ	SMA/Pin	BT-54-401D <input type="button" value="Add to RFQ"/>
30 kHz	85 GHz	4.0	500	1	25	30	2.00:1 Typ	SMA/Pin	BT-55-401D <input type="button" value="Add to RFQ"/>

更多信息，请联系我们：

地址：上海市普陀区祁连山南路 2888 号耀光中环国际 A 座 9H 室

Tel: 021-5291 8556, Fax: 021-6260 7783

www.fulai-elec.com

Email: sales@fulai-elec.com